



2009 MOTORCYCLES  
XR1200™





Whether its concrete, asphalt, pavement or blacktop, the bottomless pit of torque hits as hard as it did on racetracks a half century ago.

## MODEL FEATURES

### ENGINE

Silver Powdercoated, 1200cc Evolution® Engine  
Silver powdercoated, rubber-mounted 1200cc Evolution® engine.

### EXHAUST

2-1-2 Straight-Shot Exhaust  
Upswept high volume 2-1-2 straight shot exhaust finished in satin chrome.

### FRONT FENDER

Sport Front Fender  
The sport front fender covers a lightweight 13-spoke front wheel.

### INNER FENDER

Sport Tail Section with Separate Inner Fender  
The sport tail section with separate inner fender completes the narrow design.

### REAR TIRE

180 mm Wide Rear Tire  
Specially designed, flat track inspired Dunlop® Qualifier D209 180 mm rear tyre.

### HEADLAMP

Black Trim Ring with Black Body Headlamp  
Black body headlamp with a stylish black trim ring.

### SEAT

Two-Piece Seat  
Two-Piece Seat

### FOOTPEGS

Mid-Mounted Footpegs  
Rear-set footrests for excellent cornering clearance.

### FRAME

Narrow, Nimble Frame  
With ergonomics designed around the average European male rider, the narrow, stiff frame allows for agile performance in corners and curves.

### FUEL TANK

13.3 Liter Fuel Tank  
13.3 litre fuel tank integrated with the air intake under an XR 750™ inspired fuel tank cover.

**SPECIFICATIONS**

DIMENSIONS	U.S. UNITS
<b>Length</b>	85.40 in.
<b>Seat Height</b>	
Laden <sup>1</sup>	29.20 in.
Unladen	30.50 in.
<b>Ground Clearance</b>	5.80 in.
<b>Rake Steering Head/Trail</b>	29.3° / 5.12 in.
<b>Wheelbase</b>	59.80 in.
<b>Fuel Capacity</b>	3.50 gal.
<b>Oil Capacity</b>	2.80 qts.
<b>Weight</b>	
Dry Weight	562.00 lbs.
Running Order	580.00 lbs.

POWERTRAIN	
<b>Engine <sup>2</sup></b>	Air-cooled, Evolution®
<b>Displacement</b>	73.40 cu. in.
<b>Bore x Stroke</b>	3.500 in. x 3.812 in.
<b>Engine Torque <sup>3</sup></b>	73.91 ft lbs @ 4000 rpm
<b>Fuel System <sup>4</sup></b>	Electronic Sequential Port Fuel Injection (ESPFI)
<b>Compression Ratio</b>	10.0:1
<b>Miles Per Gallon <sup>5</sup></b>	
ESPFI	53 hwy / 38 city
<b>Primary Drive</b>	Chain, 57/34 ratio
<b>Gear Ratio (overall)</b>	
1st	10.782
2nd	7.702
3rd	5.728
4th	4.748
5th	4.071
6th	N/A

**WHEELS/TIRES**

<b>Wheels <sup>6</sup></b>	
Front	Black, 3-Spoke Cast Aluminum
Rear	Black, 3-Spoke Cast Aluminum
Wheel Option	N/A
<b>Tire Size</b>	
Front	120/70ZR18 M/C
Rear	180/55ZR17 M/C

**ELECTRICAL**


<b>Instruments</b>	Unique compact instruments with prominent white faced tachometer, digital speedo, dual trip meter and clock
<b>Indicator Lamps <sup>7</sup></b>	Hazard warning lights operated by turn signal controls; High beam, neutral, low oil pressure, turn signals, engine diagnostics, low fuel warnings, low battery, security system
<b>Reverse Function</b>	N/A

**CHASSIS**


<b>Brakes</b>	Dual 4-Piston, fixed front, single-piston floating rear
<b>Parking Brake</b>	N/A
<b>Lean Angle (per SAEJ1168)</b>	40° / 39°
<b>Exhaust System</b>	Upswept, high-volume 2-1-2 straight shot exhaust system finished in satin chrome




COLOR OPTIONS



Vivid Black



Pewter Denim



Mirage Orange Pearl

--	--	--	--	--	--

PRICING<sup>®</sup>

**MSRP**

Vivid Black	\$ 10799
Color	\$ 11079
Twotone	N/A
Custom Color	N/A
Anodized	N/A
<b>Wheel Option</b>	N/A
<b>Chrome Engine Covers Option</b>	N/A
<b>Security System Option</b>	\$ 345
<b>California Emissions</b>	\$ 100
<b>Freight</b>	\$ 300
<b>ABS</b>	N/A
<b>Cruise Control</b>	N/A



1. Measurement reflects 180 lb./81.7 kg operator weight.
2. Recommended 91 octane or higher fuel (R+M)/2.
3. Values shown are nominal. Performance varies by country and region.
4. Standard and optional fuel systems may vary by country.
5. Estimated from fuel economy tests on a sample motorcycle from the corresponding family conducted by HarleyDavidson under ideal laboratory conditions. Not all motorcycle models undergo fuel economy testing. Fuel economy and mileage may vary among motorcycle models within a family. Your mileage may vary depending on your personal riding habits, weather conditions, trip length, vehicle condition and vehicle configuration and other conditions. Break-in mileage may vary.
6. Standard and optional wheels may vary by country and region.
7. North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.
8. Prices listed are the Manufacturer's Suggested Retail Prices. Options such as color are available at additional cost. Prices exclude dealer setup, taxes, title and licensing and are subject to change. Dealer prices may vary.

---

Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered.

All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed.

Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation.

Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information.

All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

